

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** THERMAGUARD CUI 650
- **Article number:** H18-1
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU19 Building and construction work
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
 PROC7 Industrial spraying
 PROC10 Roller application or brushing
 PROC19 Manual activities involving hand contact
- **Application of the substance / the mixture** solvent based, one component siloxane coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Performance Polymers EMEA B.V.
 Snekerkweg 57
 8912 AA Leeuwarden - Netherlands
 Tel +31(0)208208370
- **Further information obtainable from:** msds@pp-bv.com
- **1.4 Emergency telephone number:**
 National Poisoning Information Center (NVIC) - Bilthoven, the Netherlands
 + 31 (0)30 2748888 (only intended to inform physicians of accidental poisonings)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 3 H226 Flammable liquid and vapour.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
 xylene
- **Hazard statements**
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 P210 Keep away from open flames. - No smoking.
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**
Percentages of the components are expressed as a percentage by weight

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37-xxxx	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 2)

- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Recommended storage temperature:** 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:
1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm
	Long-term value: 221 mg/m ³ , 50 ppm
	Skin

DNEL (Derived No Effect Level) for workers:
1330-20-7 xylene

Dermal	Long-term - systemic effects, worker	180 mg/kg bw/day (worker)
Inhalative	Acute - systemic effects, worker	289 mg/m ³ (worker)
	Acute - local effects, worker	289 mg/m ³ (worker)
	Long-term - systemic effects, worker	77 mg/m ³ (worker)

7440-66-6 zinc powder -zinc dust (stabilized)

Dermal	Long-term - systemic effects, worker	83 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker	5 mg/m ³ (worker)

1314-13-2 zinc oxide

Dermal	Long-term - systemic effects, worker	83 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker	5 mg/m ³ (worker)

DNEL (Derived No Effect Level) for the general population:
1330-20-7 xylene

Oral	Long-term - systemic effects, general population	1.6 mg/kg bw/day (general population)
Dermal	Long-term - systemic effects, general population	108 mg/kg bw/day (general population)
Inhalative	Acute - systemic effects, general population	174 mg/m ³ (general population)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 3)

	Acute - local effects, general population	174 mg/m ³ (general population)
	Long-term - systemic effects, general population	14.8 mg/m ³ (general population)
7440-66-6 zinc powder -zinc dust (stabilized)		
Oral	Long-term - systemic effects, general population	0.83 mg/kg bw/day (general population)
Dermal	Long-term - systemic effects, general population	83 mg/kg bw/day (general population)
Inhalative	Long-term - systemic effects, general population	2.5 mg/m ³ (general population)
1314-13-2 zinc oxide		
Oral	Long-term - systemic effects, general population	0.83 mg/kg bw/day (general population)
Dermal	Long-term - systemic effects, general population	83 mg/kg bw/day (general population)
Inhalative	Long-term - systemic effects, general population	2.5 mg/m ³ (general population)
· PNEC (Predicted No Effect Concentration) values:		
1330-20-7 xylene		
	Aquatic compartment - freshwater	0.327 mg/L (not specified)
	Aquatic compartment - marine water	0.327 mg/L (not specified)
	Aquatic compartment - water, intermittent releases	0.327 mg/L (not specified)
	Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (not specified)
	Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (not specified)
	Terrestrial compartment - soil	2.31 mg/kg dw (not specified)
	Sewage treatment plant	6.58 mg/L (not specified)
7440-66-6 zinc powder -zinc dust (stabilized)		
	Aquatic compartment - freshwater	0.0206 mg/L (not specified)
	Aquatic compartment - marine water	0.0061 mg/L (not specified)
	Aquatic compartment - sediment in freshwater	117.8 mg/kg sed dw (not specified)
	Aquatic compartment - sediment in marine water	56.5 mg/kg sed dw (not specified)
	Terrestrial compartment - soil	35.6 mg/kg dw (not specified)
	Sewage treatment plant	0.1 mg/L (not specified)
1314-13-2 zinc oxide		
	Aquatic compartment - freshwater	0.0206 mg/L (not specified)
	Aquatic compartment - marine water	0.0061 mg/L (not specified)
	Aquatic compartment - sediment in freshwater	117.8 mg/kg sed dw (not specified)
	Aquatic compartment - sediment in marine water	56.5 mg/kg sed dw (not specified)
	Terrestrial compartment - soil	35.6 mg/kg dw (not specified)
	Sewage treatment plant	0.1 mg/L (not specified)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Immediately remove all soiled and contaminated clothing
Provide readily accessible eye wash stations and safety showers.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 4)

Protection of hands:


Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

PVA gloves

Penetration time of glove material

KCL Vitoject 890

breakthrough time > 480 min.

thickness: 0,7 mm

at limited contact

KCL Camatril 730

breakthrough time 120 min.

thickness: 0,4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials:

Neoprene gloves

Disposables

Eye protection:


Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist.

If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves.

For further information on materials and design requirements and test methods consult the European standard EN 1149.

Limitation and supervision of exposure into the environment

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value:	Not determined.
------------------	-----------------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137 °C

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 5)

· Flash point:	30 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	500 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	7 Vol %
· Vapour pressure at 20 °C:	6.7-8.2 hPa
· Density at 20 °C:	1.97 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic at 20 °C:	550 mPas
· Kinematic:	at 40 °C: > 20,5 mm ² /s
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
7440-66-6 zinc powder -zinc dust (stabilized)		
Oral	LD50	>2,000 mg/kg (rat)
1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 6)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1330-20-7 xylene

EC50/72 h | 1-10 mg/l (Algae, Growth inhibition test)

EC50/48 h | 1-10 mg/l (Daphnia magna)

LC50/96 h | 1-10 mg/l (Oncorhynchus mykiss)

7440-66-6 zinc powder -zinc dust (stabilized)

LC50/96 h | 0.24 mg/l (Oncorhynchus mykiss)

LC50/48 h | 0.068 mg/l (Daphnia magna)

0.645-1 mg/l (Penaeus chinensis (fleshy prawn))

1314-13-2 zinc oxide

EC50/72 h | 0.21 mg/l (Algae, Growth inhibition test)

EC50/48 h | 0.67 mg/l (Ceriodaphnia dubia)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Ecotoxicological effects:

· **Remark:** Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

(Contd. on page 8)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020




Trade name: THERMAGUARD CUI 650

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

Transport in accordance with ADR/RID, IMDG and ICAO/IATA.

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (zinc powder -zinc dust (stabilized), zinc oxide), MARINE POLLUTANT PAINT
· 14.3 Transport hazard class(es) · ADR/RID/ADN, IMDG	<div style="display: flex; align-items: center; gap: 10px;">   </div> · Class · Label
· IATA	<div style="display: flex; align-items: center; gap: 10px;">  </div> · Class · Label
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.12.2020

Version: 4

Revision: 05.12.2020

Trade name: THERMAGUARD CUI 650

(Contd. of page 8)

· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS
--------------------------	--

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Classification according to Regulation (EC) No 1272/2008**
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- **Contact:** S. Reynolds
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - dermal – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- **Sources**
 - ECHA European Chemical Agency - <http://echa.europa.eu/information-on-chemicals>
 - SDS of raw materials supplied by producer/supplier.
- *** Data compared to the previous version altered.**
Date previous version: 11-04-2019